

60x60 slim cassette

- > Combined with SDI outdoor unit
- > 360° air distribution in the Euro-grid with installation height of just 256 mm
- > Efficiency up to A++; enhanced energy savings via presence sensor option
- > Integrated drain pump (850 mm); prepared for external fresh air supply
 - > Accessories required: remote control + panel



Super Digital Inverter – 1-phase – 60x60 slim cassette

LIGHT BUSINESS / RAV

| INDOOR UNIT | | | RAV-HM561MUTP-E |
|---|-----------|----|-----------------|
| OUTDOOR UNIT | | | RAV-GP561ATW-E |
| Cooling capacity | kW | ❄️ | 5,00 |
| Cooling range (min.-max.) | kW | ❄️ | 1,20 - 5,60 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,19/1,22/1,97 |
| Energy efficiency EER | W/W | ❄️ | 4,10 |
| Energy efficiency SEER | | ❄️ | 7,73 |
| Energy efficiency class | | ❄️ | A++ |
| Outdoor temperature operating range (min. - max.) | °C | ❄️ | -15 / +52 |
| Heating capacity | kW | 🔥 | 5,60 |
| Heating range (min.-max.) | kW | 🔥 | 0,90 - 8,10 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,16/1,30/2,76 |
| Energy efficiency COP | W/W | 🔥 | 4,31 |
| Energy efficiency SCOP | | 🔥 | 4,98 |
| Energy efficiency class | | 🔥 | A++ |
| Outdoor temperature operating range (min. - max.) | °C | 🔥 | -27 / +15 |
| Power supply | V/Ph+N/Hz | | 220-240/1+N/50 |
| Recommended fusing | A | | 16 |

| INDOOR UNIT | | | RAV-HM561MUTP-E |
|-------------------------------------|-------|----|-----------------|
| Airflow | m³/h | | 780/870/1050 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 28/29/32 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 28/29/32 |
| Dimensions (HxWxD) | mm | | 256 x 840 x 840 |
| Weight | kg | | 20 |
| Panel dimensions (HxWxD) | mm | | 30 x 950 x 950 |
| Panel weight | kg | | 4,2 |

| OUTDOOR UNIT | | | RAV-GP561ATW-E |
|-------------------------------------|-----------|----|-----------------|
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 46 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 48 |
| Suction gas pipe diameter | mm (inch) | | 12,7 (½) |
| Liquid pipe diameter | mm (inch) | | 6,4 (¼) |
| Pipe length (min.) | m | | 5 |
| Pipe length (max.) | m | | 50 |
| Height difference (max.) | m | | 30 |
| Compressor type | | | Twin-Rotary |
| Refrigerant | | | R32 |
| Refrigerant charge | kg | | 1,35 |
| Dimensions (HxWxD) | mm | | 630 x 799 x 299 |
| Weight | kg | | 45 |